

- Product type ID code:
WOOD 68 – Windows and balcony doors.
- Designation identifying the construction product as per the Regulation of the European Parliament and the EU Council No. 305/2011, art. 11, item 4:
Identification number on the label placed on the window/door (XXXXXX/XX)
- Intended use (purpose) provided for by the manufacturer:
Designed for use in buildings as per the Regulation of the European Parliament and the EU Council No. 305/2011, art. 2, item 3.
- Manufacturer's name and address as per the Regulation of the European Parliament and the EU Council No. 305/2011, art. 11, item 5.
CDM Sp. z o.o., ul. Wojska Polskiego 112 A, 16-400 Suwałki, www.cdm-drewno.pl
- System of assessment and verification of performance constancy as per the Regulation of the European Parliament and the EU Council No. 305/2011, Annex V:
System 3
- The name and identification number of the notified body:
PfB GmbH & Co. Prüfzentrum für Bauelemente KG - Certificate No. 08/07-A192-Z1
- Declared performance values according to EN 14351-1:2006 + A1:2010:

Essential characteristics		Performance properties			
Water tightness		7A			
Dangerous substances		does not contain			
Resistance to wind load		C5			
Load-bearing capacity of safety devices		point 4.8 met			
Acoustic properties [dB] ¹⁾		F≤2.7m ² Rw=34 (-1;-5) 2.7m ² <F<3.6m ² Rw=33 (-1;-5) 3.6m ² <F<4.6m ² Rw=32 (-1;-5) 4.6m ² <F Rw=31 (-1;-5)			
Heat transfer Uw [W/m ² K]		2)			
Ug [W/m ² K]		Spacer bars:			
		Aluminum	Warm Stainless steel	Warm Swisspacer Advance	Warm Swisspacer Ultimate
Softwood ³⁾ up to 0.57g/cm ³	1,1	1,4	1,33	1,29	1,27
	1,0	1,33	1,26	1,23	1,21
	0,7	1,15	1,06	1,02	1,0
Hardwood ⁴⁾ 0.58g/cm ³ ÷ 0.72g/cm ³	1,1	1,53	1,46	1,43	1,41
	1,0	1,46	1,39	1,36	1,34
	0,7	1,28	1,20	1,15	1,13
Solar coefficient g		NPD			
Air permeability		4			

1) The Rw value determined in accordance with paragraph B3 of Annex B to EN 14351-1 + A1, for glazed windows with a value of Rw=32dB.

2) The UW value determined for a reference window 1.23m x 1.48m with a different type of glazing and a different type of spacer.

3) Types of wood: Meranti, Larch, Pine, Spruce, etc.

4) Types of wood: Oak, Framire, Rosewood, Sapele, etc.

- The performance properties of the product referred to in items 1 and 2 are consistent with those declared in item 7.
- This declaration of performance is issued under the sole responsibility of the manufacturer referred to in item 4.


On behalf of the manufacturer signed by:

Chairman of the Board - Grzegorz Król

.....
 (name and surname, position)

Suwałki 01.07.2013

.....
 (city, issuing date)

PREZES ZARZĄDU

 mgr inż. Grzegorz Król
 (signature)